

Linux Problems

NFS won't start

In [Devuan](#) Beowulf, I installed nfs-common so I could mount some nfs shares, but the mount on boot does not work. After boot is complete, I can mount my nfs shares manually.

Looking in the logs, I see the following error: **/run/rpcbind not owned by root failed!**

This is caused by an incorrect path (see <https://lists.debian.org/debian-user/2018/10/msg01012.html>), which can be fixed by the following:

```
echo 'PATH="$PATH:/usr/bin"' >> /etc/default/rpcbind
```

/etc/default/rpcbind is called in the startup scripts, so this will add /usr/bin to the path when nfs is started.

sort gives unexpected results

Ran into a problem on Devuan (Debian) Linux where sort did not give expected results.

INPUT:

[f.dat](#)

```
02-175CB:D
022C11EE:D
02-2D270:D
```

```
sort f.dat
```

returns

```
02-175CB:D
022C11EE:D
02-2D270:D
```

Run under FreeBSD and also

```
perl -e '@a=<>;chomp(@a);print join($/,sort @a).$/;' <f.dat
```

returns

```
02-175CB:D
```

```
02-2D270:D
022C11EE:D
```

Which I expected.

Under Linux, you can get the same results by setting the collate first:

```
LC_COLLATE=C sort f.dat
```

I tracked this down from a similar problem using `ls` on Linux. See <https://unix.stackexchange.com/questions/35469/why-does-ls-sorting-ignore-non-alphanumeric-characters>.

Links

- <https://lists.debian.org/debian-user/2018/10/msg01012.html>
- <https://unix.stackexchange.com/questions/35469/why-does-ls-sorting-ignore-non-alphanumeric-characters>

From:

<https://kb.unixservertech.com/> - **Unix Server Tech Knowledge Base**

Permanent link:

<https://kb.unixservertech.com/start/debugging/linux?rev=1654137996>

Last update: **2022/06/02 02:46**

